

ENERGY EFFICIENCY

Thermal Transmission Coefficient

U_w from 0.9 (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: **55 mm.**

Maximum acoustic insulation: **Rw = 43 dB.**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmosphere agents

Air permeability (UNE-EN 12207:2000):

Class 4

Water tightness (UNE-EN 12208:2000):

Class 9A

Wind resistance (UNE-EN 12210:2000):

Class C5

*Reference test: 4.0 x 2.4 m. 2 sashes

SECTIONS	Frame 160.6 mm Triple rail 251 mm Sash 70 mm	EXTRUSION ALLOY 6063 T-5
PROFILE THICKNESS	Door 2.0 mm	POLYAMIDE STRIP LENGTH Polyamide 6.6 reinforced with 25% fiberglass: Frame 35 mm Sash 24 mm
MAXIMUM DIMENSIONS	Width (L) = 3,300 mm Height (H) = 3,300 mm	OPENING POSSIBILITIES Sliding 2, 3, 4 and 6 sashes. Optionally monorail (1 sash+1 fixed) Optionally triple rail.
MAXIMUM WEIGHT/SASH	400 Kg	
DRAINAGE	Optionally drainage system and drainage grid made of stainless steel	

Please consult regarding maximum weight and dimensions according to types

FINISHES

Colour powder coating
(RAL, mottled, rough...)

According to Qualicoat >60 micras

Wood effect powder coating

According to Qualideco standard

Anodized

According to Ewwa Euras
Standard Class 15

Optionally Class 20 and 25

Optionally bicoloured

